## TObject

| | | |
|---|---|---|
| fUniqueID | kNotDeleted | kWriteDelete |
| fBits | kZombie | fgIsA |
| fgDtorOnly | kBitMask | |
| fgObjectStat | kSingleKey | |
| kIsOnHeap | kOverwrite | |

| | | |
|---|---|---|
| MakeZombie | GetOption | operator new |
| DoError | GetObjectInfo | operator new[] |
| TObject | GetTitle | operator delete |
| TObject | HandleTimer | operator delete[] |
| operator= | Hash | SetBit |
| AppendPad | InheritsFrom | SetBit |
| Browse | InheritsFrom | ResetBit |
| ClassName | Inspect | TestBit |
| Clear | IsFolder | TestBits |
| Clone | IsEqual | InvertBit |
| Compare | IsSortable | Info |
| Copy | IsOnHeap | Warning |
| Delete | IsZombie | Error |
| DistancetoPrimitive | Notify | SysError |
| Draw | Is | Fatal |
| DrawClass | Paint | AbstractMethod |
| DrawClone | Pop | MayNotUse |
| Dump | Print | GetDtorOnly |
| Execute | Read | SetDtorOnly |
| Execute | RecursiveRemove | GetObjectStat |
| ExecuteEvent | SavePrimitive | SetObjectStat |
| FindObject | SetDrawOption | Class |
| FindObject | SetUniqueID | Class_Name |
| GetDrawOption | UseCurrentStyle | IsA |
| GetUniqueID | Write | ShowMembers |
| GetName | operator new | Streamer |
| GetIconName | operator new[] | |

## TRef

| |
|---|
| fPID |
| fgExecs |
| fgObject |
| kNotComputed |
| fgIsA |

| |
|---|
| TRef |
| TRef |
| TRef |
| operator= |
| operator= |
| AddExec |
| GetObject |
| GetListOfExecs |
| GetPID |
| IsValid |
| SetAction |
| SetAction |
| SetObject |
| Class |
| Class_Name |
| IsA |
| ShowMembers |
| Streamer |